

Innovative system integrated Face readers by RBH are available with fingerprint reader, MIFARE, DESFire, and QR recognition.

RBH-BFR-FACE25Q SERIES

The BFR-FACE25Q-DNB facial reader delivers unmatched performance, user-friendly operation, and exceptionally fast processing and authentication speeds. This is made possible by its dual-camera system and IR technologies, ensuring outstanding accuracy. Compatible with other authentication methods such as fingerprint readers and QR code recognition, the BFR-FACE25Q-DNB is a versatile reader ideal for a wide range of environments.



Fully integrated with:



How to order: RBH-BFR-FACE25-D for sector RBH-BFR-FACE25-S for CSN

Specifications	
Processor	ARM based 32 bits
Verification mode	Face / Fingerprint / PIN code/ Card/ QR
Face / Finger / Card capacity	10,000
System log	10,000
Web Base Management	Yes
Verification speed	< 0.5 second
Tamper	Yes
Scan distance	12 in (30 cm) - 31 in (80 cm)
Read Range	CSN: Keytag: 4" (100mm) - Card: 6" (150mm) Sector: Keytag: 1.5" (38mm) - Card: 3" (76mm) QR: 4" (100mm)
TCP/IP	Yes (Static IP/DHCP (Client)
Integrated Reader	SECTOR / CSN for MIFARE Classic / Plus / DESFire EV1/2/3 (RBH-BFR-FACE15Q-D for sector & RBH-BFR-FACE15Q-S for CSN)

Communication / User Interface

Communication method	TCP/IP, Weigand, OSDP ver. 1 & 2
Communication environment	LAN / WAN
Ethernet Interface	10/100M Base-T, Auto Crossover
Audible speaker	16 bits mono
TFT Color LCD	4.3 inches touch screen
Tamper	Yes
Electrical / Physical data	
Operation voltage	12V DC / 1.5A
Operation temperature	32°F (0°C) - 122° F (50°C)
Operation humidity	10% - 80%RH
Dimensions	4.8 x 7.5 x 2.8 inc (123 x 185 x 89 mm)
Weight	1.4 lb (590 gr)

*Specifications are subject to change without notice.



RBH Access Technologies, Inc. 2 Automatic Road, Suite 108 Brampton ON L6S 6K8, Canada

> 1-905-790-1515 1-905-790-3680

info@rbh-access.com



