

AxiomV™



AX-UNC 100 Series Universal Network Controller

Processor / Memory	32-bit Processor / 2MB
Memory Capacity: Cards	50,000
Event Log	30,000
Firmware	Flash
Communications	Built in TCP/IP, RS-485
Com Ports	1 RS-485 programmable
Cable Requirement	Shielded, twisted pair, 20 - 22 AWG; 4,000 ft (1,200 m) total
Doors	Available in 1 or 2 Doors
On board Reader Ports	1 DOOR: 1 Wiegand read in / 1 Wiegand read out for one door with up to 5 concurrent card formats 2 DOOR: 2 Wiegand ports for up to 2 doors with up to 5 concurrent card formats
Audio/Visual Controls	Red and Green reader LED, audible controls
Cable Requirement	Shielded, stranded 6 or 8 conductor, 20 - 22 AWG; Max 500 ft (150 m) @ 20 AWG
Programmable Inputs	4 + Cabinet Tamper Input
Circuit Types	4 State Monitoring
Programmable Outputs	4 (2 relays + 2 open collector outputs)
Relays	Form C relays, SPDT, 5 A @30 VDC, dry contacts; Fail Safe/Secure programmable
Power : Input	13.8VDC @1.5 A
Circuit protection	Thermal - Power In, Power Out, Reader Power
PoE (optional)	IEEE 802.3at compliant : 25.5W; Other : 30W
Built in Backup Battery Charger	From PoE
Auxiliary Voltage Outputs	12-14 VDC @ 500 mA
Dimensions Circuit board only	6" H x 5.3" W x 1.5" D
Metal shell	7.75" H x 5.5" W x 1.5" D
Operating environment	Temperature: 0 to 70°C (32 -158°F); Humidity: 20 to 85% RH (non-condensing)
Certifications	 <small>Listings/certifications are product specific. Specifications subject to change without notice.</small>

The RBH-UNC-100 series is a welcome addition to the new generation of powerful and reliable AxiomV hardware. The one or two door native TCP/IP controllers come equipped with onboard battery backup chargers and accommodate up to 16 individual IOC-16 input/output controllers or 254-SafeSuite keypads. The units are expandable to 7 or 8 doors respectively, using 3 additional RC-2 or NIRC/NURC controllers. The UNC-100 also features a 32-bit processor with encryption and expanded memory. The UNC100-132 models come equipped with IEEE 802.3at compliant PoE capability, further increasing this UNC series' award-winning efficiency.

PoE Features

- IEEE 802.3at Compliant
- 30 Watt power rating
- Built-in battery backup with charger
- Operates with non-compliant PoE+PSEs
- Available auxiliary power output

Models Available

	PoE	2 Door	Certified	Power Supply and Enclosure
122M				
122M-2D		✓		
122S				✓
122S-2D		✓		✓
122C			✓	✓
122C-2D		✓	✓	✓
132M	✓			
132M-2D	✓	✓		
132S	✓			✓
132S-2D	✓	✓		✓
132C	✓		✓	✓
132C-2D	✓	✓	✓	✓



WWW.RBH-ACCESS.COM

© RBH Access Technologies, Inc. 2016