



## Touch Screen Face Recognition **RBH-BFR-FACE15-DNB series**

Innovative system integrated Face readers by RBH are available with Mifare, Desfire, NFC & Blue-tooth (BLE) readers.

[www.rbh-access.com](http://www.rbh-access.com)

# RBH-BFR-FACE15-DNB SERIES

Users will benefit from its unparalleled performance, ease of use, precision and fast matching speed. This Face reader features a highly accurate. The user will also benefit from the advanced matching algorithm and audio-visual indications for acceptance & rejection of Face.



Compact design

OSDP

10.000 user face detection

Dual camera fast recognition

User friendly touch screen

Fully integrated with



With the technology of



## Specifications

Processor	ARM based 32 bits
Verification mode	Face/ Pin code/ Card/ Mobile
Face / Card capacity	10.000
System log	10,000
Web Base Management	Yes
Verification speed	< 0.5 second
Tamper	Yes
Scan distance	12 in (30 cm) - 31 in (80 cm)
TCP/IP	Yes (Static IP/DHCP (Client))
Integrated Reader	SECTOR / CSN for MiFARE Classic / Plus / DESFire EV1/2/3 (RBH-BFR-FACE-D for sector & RBH-BFR-FACE-S for CSN)
Communication data	
Communication method	TCP/IP, Weigand, OSDP ver. 1 & 2
Communication environment	LAN / WAN
Ethernet Interface	10/100M Base-T, Auto Crossover
Indication data & User interface	
Buzzer	Single Tone
TFT Color LCD	4.3 inches touch screen
Anti-Tampering switch	Yes
Electrical data conditions	
Operation voltage	12V DC / 1.5A
Operation temperature	32°F (0°C) - 122° F (50°C)
Operation humidity	10% - 80%RH
Physical data	
Dimensions	4.8 x 6.5 x 2.8 inc (123 x 166 x 72 mm)
Weight	1.4 lb (650 gr)

\*Specifications are subject to change without notice.

## Order:


RBH-BFR-FACE15-D for sector  
RBH-BFR-FACE15-S for CSN



RBH Access Technologies, Inc.  
2 Automatic Road, Suite 108  
Brampton ON L6S 6K8, Canada

1-905-790-1515  
1-905-790-3680

[info@rbh-access.com](mailto:info@rbh-access.com)



[www.rbh-access.com](http://www.rbh-access.com)