



Keypad Reader

RBH-NK86G Series

Award-winning Single Gang Mount 13.56mhz Reader with Keypad/Pinpad for dual authentication or Pin operation

www.rbh-access.com

RBH-NK86G SERIES

The RBH-NK86G Single Gang mount reader reads 13.56mhz Mifare or Desfire encrypted cards and tags for the highest level of security. The readers come standard with 50 bit wiegand output and can be ordered with 34 bit output for third party systems. For ultra secure installations readers can be ordered with OSDP1 & 2 capability. All readers are potted for indoor and outdoor use. Readers can be ordered for Card and Pin OR Card or Pin operation (standard output is 50 bit RBH with 8 bit burst)



MiFare CSN

MiFARE SECTOR

DESFire EV1-3

IP-65






PIN Multi function

Compatible with



Most 3rd Party Access control Solutions

Specifications

Reader Reference	RBH-NK86G SERIES
Card Types	Most MiFARE credentials (CLASSIC / PLUS / DESFire EV1, EV2, EV3)
Communication	Wiegand - OSDP (Ver 1&2)
Dimensions	4.75" X 3.125" X .75" (119mm X 80mm X 20mm)
Housing	ABS
Read Range	CSN: Keytag: 4" (100mm) - Card: 6" (150mm) Sector: Keytag: 1.5" (38mm) - Card: 3" (76mm)
Cabling Wiegand	500' (152m) max, 18 - 22 AWG, 6-7 conductor shielded cable
Cabling OSDP (Ver 1&2)	RS485: 4000' (1219m) max, 20 - 22 AWG, 1 twisted pair, shielded, stranded Power: 2000' (610m) max, 18 - 22 AWG 2 conductor stranded
Operating Temperature	-40° F to +158° F (-40° C to + 70° C)
Color	Black
Indicators	Tri-color LED, Built-in Piezo sounder
Frequency	13.56 MHz / Bluetooth
Connector	18 inch (47 cm) Pigtail
Rating	IP-65
Weight	5.29 oz. (150 gr)
Power	12 - 15 VDC @ 100 mA
Certifications	    

*Specifications are subject to change without notice.

Order:

RBH-NK86G-D for sector
RBH-NK86G-S for CSN



RBH Access Technologies, Inc.
2 Automatic Road, Suite 108
Brampton ON L6S 6K8, Canada

1-905-790-1515
1-905-790-3680

info@rbh-access.com

