



blueLINE Mullion Mount Reader  
**RBH-M45G Series**

Ensures seamless, high-security access with a future-ready design built for evolving security needs.

[www.rbh-access.com](http://www.rbh-access.com)

# RBH-M45G SERIES

The RBH-M45G delivers advanced access control with support for 13.56MHz Mifare and Desfire encrypted cards and tags.

Compatible with 50-bit Wiegand or 34-bit output for third-party systems, and for elevated security, OSDP1 & 2 support is available. Designed for indoor and outdoor reliability, the RBH-M45G ensures seamless, high-security access in any environment.



MiFare CSN

MIFARE SECTOR

DESFire EV1-3

IP-65






Tri-Color LED indicator

Compatible with:



Most 3rd Party Access control Solutions

## Specifications

Reader Reference	RBH-M45G SERIES
Card Types	Most MiFARE credentials (CLASSIC / PLUS / DESFire EV1, EV2 (EAL 5+), EV3 (EAL 5+))
Communication	Wiegand - OSDP (Ver 1&2)
Dimensions	3.87" X 2" X .75" (100mm X 51mm X 20mm)
Housing	ABS
Read Range	<b>CSN:</b> Keytag: 4" (100mm) - Card: 6" (150mm) <b>Sector:</b> Keytag: 1.5" (38mm) - Card: 3" (76mm)
Cabling Wiegand	500' (152m) max, 18 - 22 AWG, 6-7 conductor shielded cable
Cabling OSDP (Ver 1&2)	RS485: 4000' (1219m) max, 20 - 22 AWG, 1 twisted pair, shielded, stranded Power: 2000' (610m) max, 18 - 22 AWG 2 conductor stranded
Operating Temperature	-40° F to +158° F (-40° C to + 70° C)
Color	Black
Indicators	Tri-color LED, Built-in Piezo sounder
Frequency	13.56 MHz
Connector	18 inch (47 cm) Pigtail
Rating	IP-65
Weight	4.06 oz. (115 gr)
Power	12 - 15 VDC @ 100 mA
Certifications	    

\*Specifications are subject to change without notice.

Order:

RBH-M45G-D for sector  
RBH-M45G-S for CSN

With the technology of:





RBH Access Technologies, Inc.  
2 Automatic Road, Suite 108  
Brampton ON L6S 6K8, Canada

1-905-790-1515  
1-905-790-3680

[info@rbh-access.com](mailto:info@rbh-access.com)

